

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
22 April 2004 (22.04.2004)

PCT

(10) International Publication Number
WO 2004/033835 A1

- (51) International Patent Classification⁷: **E05G 1/026**,
E05D 15/58, E06B 5/11
- (21) International Application Number:
PCT/AU2003/001321
- (22) International Filing Date: 8 October 2003 (08.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2002951987 9 October 2002 (09.10.2002) AU
2003902027 30 April 2003 (30.04.2003) AU
- (71) Applicant (for all designated States except US): **LOK-
AWAY PTY. LTD.** [AU/AU]; Factory 9, 151-159 Princes
Highway, Hallam, Victoria 3803 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **DUNSTAN, Brett**
[AU/AU]; Factory 9, 151-159 Princes Highway, Hallam,
Victoria 3803 (AU).
- (74) Agent: **KRAEMER, Michael**; Sandercock & Cowie,
Suite 8c, 50-54 Robinson Street, Dandenong, Victoria
3175 (AU).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: SECURITY DOOR AND FRAME CONSTRUCTION



(57) **Abstract:** This security door construction is applicable to safes, factory doors and house doors. An offset hinge assembly allows the door to swing open and closed and also to slide in and out of a door slot in the door frame at the closing edge of the door. In the construction of a safe, hooks on the inside of the door enter slots in upstands inside the safe and engage and disengage through the sliding motion. House doors and screen doors use a hinge assembly which operates in the same way as the safe. One pair of hinges are fixed to the frame and the second pair of hinges are fixed to the door. The frame and door pairs are connected by a rod or tube which ensures that the hinge axis of the door pair remains parallel to the hinge axis of the frame pair. A door locking mechanism is actuated by a conventional pneumatic door closer. A gas strut supplies the thrust to cause the mechanism to slide the door into the door slot when the door closer brings the door into register with the door slot.